

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/749,867	12/31/2003	Yan Zhou	75622P006201	6324	
22503	7590 03/03/2006		EXAMINER		
DAVIS & ASSOCIATES			SINGH, RAMNANDAN P		
P.O. BOX 1093 DRIPPING SPRINGS, TX 78620			ART UNIT	PAPER NUMBER	
	,		2646		
			DATE MAILED: 03/03/2000	DATE MAILED: 03/03/2006	

Please find below and/or attached an Office communication concerning this application or proceeding.

	1 A 11 - 41 N -	
	Application No.	Applicant(s)
	10/749,867	ZHOU, YAN
Office Action Summary	Examiner	Art Unit
	Ramnandan Singh	2646
The MAILING DATE of this communication ap Period for Reply	opears on the cover sheet with the c	orrespondence address
A SHORTENED STATUTORY PERIOD FOR REPI WHICHEVER IS LONGER, FROM THE MAILING I - Extensions of time may be available under the provisions of 37 CFR 1, after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period: - Failure to reply within the set or extended period for reply will, by stature Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATION .136(a). In no event, however, may a reply be tin d will apply and will expire SIX (6) MONTHS from tte, cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).
Status		
 1) Responsive to communication(s) filed on 03. 2a) This action is FINAL. 2b) This action for allowed closed in accordance with the practice under 	is action is non-final. ance except for formal matters, pro	
Disposition of Claims		
4) Claim(s) 1-20 is/are pending in the application 4a) Of the above claim(s) is/are withdra 5) Claim(s) is/are allowed. 6) Claim(s) 1-20 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/ Application Papers	awn from consideration. /or election requirement.	,
9) The specification is objected to by the Examin 10) The drawing(s) filed on is/are: a) ac Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the E	ccepted or b) objected to by the lessenge of common or by the lessenge of the drawing of the dra	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreig a) All b) Some * c) None of: 1. Certified copies of the priority documer 2. Certified copies of the priority documer 3. Copies of the certified copies of the pri application from the International Bures * See the attached detailed Office action for a list	nts have been received. nts have been received in Applicati ority documents have been receive au (PCT Rule 17.2(a)).	on No ed in this National Stage
Attachment(s) 1) D Notice of References Cited (PTO-892)	4) 🔲 Interview Summary	(PTO-413)
 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08 Paper No(s)/Mail Date <u>Jan. 03, 2006</u>. 	Paper No(s)/Mail Da	ate Patent Application (PTO-152)

Application/Control Number: 10/749,867 Page 2

Art Unit: 2646

DETAILED ACTION

Response to Arguments

1. Applicant's arguments filed Jan. 03, 2006 have been fully considered but they are not persuasive.

Applicant's argument---" Lee does not teach or suggest an integrated circuit driver that combines a downstream voice signal and downstream data signal into a common downstream signal for the subscriber line" on page 3.

Examiner's response---Examiner respectfully disagrees. Lee teaches: "The voiceband channel circuitry may be integrated on the same integrated circuit die as the xDSL circuitry, if a single clock is used for synchronization." [col. 8, lines 47-49]. Further Lee teaches that both the hybrid network having the receive circuit and the driver reside on the same integrated circuit die [col. 10, lines 41-63]. In addition, Lee teaches a method as to how to use synchronous sample rate conversion to drive the other clock frequencies so that multiple independent clocks can be avoided [col. 8, line 59 to col. 10, line 32].

Drawings

2. With the applicant's revised submission of the drawings, the objection to the drawings is withdrawn.

Claim Rejections - 35 USC § 102

3. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 4. Claims 1-6, 11, 12 are rejected under 35 U.S.C. 102(e) as being anticipated by Lee [US 6,944,213 B2].

The applied reference has a common assignee with the instant application.

Based upon the earlier effective U.S. filing date of the reference, it constitutes prior art under 35 U.S.C. 102(e). This rejection under 35 U.S.C. 102(e) might be overcome either by a showing under 37 CFR 1.132 that any invention disclosed but not claimed in the reference was derived from the inventor of this application and is thus not the invention "by another," or by an appropriate showing under 37 CFR 1.131.

Regarding claim 1, Lee teaches a subscriber line interface circuit apparatus shown in Fig. 2, comprising:

a driver (380) combining a downstream voice signal in a voiceband range and a downstream data signal in a non-voiceband range into a common downstream signal for a subscriber line (290); and receiver circuitry (240) coupled to provide an upstream

data signal and an upstream voice signal from an upstream signal carried by the subscriber line, wherein the driver and receiver circuitry reside on a same integrated circuit die [Figs. 1-4; col. 5, line 46 to col. 6, line 3; col. 8, lines 44-58; col. 10, lines 41-53; col. 10, line 64 to col. 7, line 9; Abstract]. In this context, Lee further teaches that the voiceband channel circuitry may be integrated on the same integrated circuit die as the xDSL circuitry, if a single clock is used for synchronization [col. 8, lines 47-49]. Lee also teaches that both the hybrid network having the receive circuit and the driver reside on the same integrated circuit die [col. 10, lines 41-63]. In addition, Lee teaches a method as to how to use synchronous sample rate conversion to drive the other clock frequencies so that multiple independent clocks can be avoided [col. 8, line 59 to col. 10, line 32].

Regarding claims 2-3 and 5-6, Lee further teaches the apparatus comprising: an upstream low pass filter providing a low pass filtered upstream signal as an upstream voice signal, wherein the upstream low pass filter resides on the integrated circuit die [Fig. 4];

a downstream low pass filter providing a low pass filtered downstream voice signal to the driver, wherein the downstream low pass filter resides on the integrated circuit die

an upstream high pass filter providing a high pass filtered upstream signal as an upstream data signal, wherein the upstream high pass filter resides on the common integrated circuit die Fig. 4]; and

a downstream high pass filter providing a high pass filtered downstream data signal to the driver, wherein the downstream high pass filter resides on the integrated circuit die [col. 5, line 59 to col.6, line 35].

Regarding claim 4, Lee further teaches the apparatus, wherein the voiceband range is from approximately 300 Hz to 4 kHz [Fig. 1]. However, it is well-known in the art.

Regarding claim 11, Lee further teaches the apparatus, wherein the non-voiceband range is greater than 25 kHz [Fig. 1]. However, it is well-known in the art.

Regarding claim 12, Lee further teaches the apparatus, wherein the downstream data signal is a discrete multi-tone encoded signal [col. 3, lines 51-57].

Claim Rejections - 35 USC § 103

- 5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 6. Claims 13-16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lee [US 6,944,213 B2] in view of Zhou et al [US 5,452,345].

Regarding claim 13, Lee teaches a subscriber line interface circuit apparatus shown in Fig. 2, comprising:

a driver (380) combining a downstream voice signal in a voiceband range and a downstream data signal in a non-voiceband range into a common downstream signal for a subscriber line (290); and receiver circuitry (240) coupled to provide an upstream data signal and an upstream voice signal from an upstream signal carried by the subscriber line, wherein the driver and receiver circuitry reside on a same integrated circuit die [Figs. 1-4; col. 5, line 46 to col. 6, line 3; col. 8, lines 44-58; col. 10, lines 41-53; col. 10, line 64 to col. 7, line 9; Abstract]. In this context, Lee further teaches that the voiceband channel circuitry may be integrated on the same integrated circuit die as the xDSL circuitry, if a single clock is used for synchronization [col. 8, lines 47-49]. Lee also teaches that both the hybrid network having the receive circuit and the driver reside on the same integrated circuit die [col. 10, lines 41-63]. In addition, Lee teaches a method as to how to use synchronous sample rate conversion to drive the other clock frequencies so that multiple independent clocks can be avoided [col. 8, line 59 to col. 10, line 32].

Lee does not teach explicitly providing a metering signal to the SLIC device.

Zhou et al teach using a metering signal generator to provide a metering signal to the downstream path and upstream path [col. 2, lines 45-68]. It may, however, be noted

that this is a teaching to one of ordinary skill in the art to apply the same to other applications.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the teachings of Zhou et al with Lee in order to provide a metering signal to continuously notify a customer of telephone charges, etc. [Zhou et al; col. 1, lines 12-16].

Regarding claim 14, Lee further teaches the apparatus, wherein the voiceband range is from approximately 300 Hz to 4 kHz [Fig. 1; col. 1, lines 47-48]. However, it is well-known in the art.

Regarding claim 15, Lee further teaches the apparatus, wherein the non-voiceband range is greater than 25 kHz [Fig. 1; col. 1, lines 48-49]. However, it is well-known in the art.

Regarding claim 16, Lee further teaches the apparatus, wherein the downstream data signal is a discrete multi-tone encoded signal [col. 1, lines51-65].

7. Claims 13-18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Bell [US 5,930,340] in view of Zhou et al [US 5,452,345], and further in view of Willcox et al [US 5,329,588].

Regarding claim 13, Bell teaches combining voice and data signals on a common carrier shown in Figs. 1 thru 3, comprising:

a driver (i.e. splitter 301) combining a downstream voice signal in a voiceband range and a downstream data signal in a non-voiceband range into a common downstream signal for a subscriber line [Figs. 1, 3;col. 4, lines 30-65; col. 6, line 44 to col. 7, line 18]; and

receiver circuitry (i.e. reverse splitter 301) coupled to provide an upstream data signal and an upstream voice signal from an upstream signal carried by the subscriber line [Fig. 3; col. 6, line 44 to col. 7, line 18].

Bell does not teach explicitly providing a metering signal to the SLIC device.

Zhou et al teach using a metering signal generator to provide a metering signal to the downstream path and upstream path [col. 2, lines 45-68]. It may, however, be noted that this is a teaching to one of ordinary skill in the art to apply the same to other applications.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the teachings of Zhou et al with Bell in order to provide a metering signal to continuously notify a customer of telephone charges, etc. [Zhou et al; col. 1, lines 12-16].

Further, Bell et does not teach expressly embodying the circuitry on an integrated circuit die.

Willcox et al teach a subscribe line interface circuit (SLIC) embodied in the form of a monolithic Integrated circuit or chip [Fig. 1; coll. 1, lines 13-20].

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the teachings of Willcox et al with Bell in order to protect the integrated splitter circuit using a die cap.

Regarding claim 14, Bell further teaches the apparatus, wherein the voicebands are below 4 kHz [col. 1, lines 51-53]. However, it is well-known in the art.

Regarding claim 15, Bell further teaches the apparatus, wherein the non-voiceband range is typically from 50kHz to 1 MHz [col. 1, lines 53-54]. However, it is well-known in the art.

Regarding claim 16, Bell further teaches the apparatus, wherein the downstream data signal is a discrete multi-tone encoded signal [col. 2, lines 23-31].

Art Unit: 2646

Regarding claims 17 and 18, Bell teaches a bi-directional splitter (301) for both upstream and downstream signals. As a result the same low pass and high pass filters apply to both directions [Fig. 3].

8. Claims 7 and 10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lee as applied to claim 1 above, and further in view of Zhou et al [US 5,452,345].

Regarding claim 7, Lee does not teach explicitly providing a metering signal to the SLIC device.

Zhou et al teach using a metering signal generator to provide a metering signal to the downstream path and upstream path [col. 2, lines 45-68]. It may, however, be noted that this is a teaching to one of ordinary skill in the art to apply the same to other applications.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the teachings of Zhou et al with Lee in order to provide a metering signal to continuously notify a customer of telephone charges, etc. [Zhou et al; col. 1, lines 12-16].

Regarding claim 10, Hjartarson et al further teach the apparatus, wherein the voice and data signals are weight coupled to the driver using an impedance generator

Art Unit: 2646

(424) in combination with LPF (422), wherein the weights permit varying the ratio of the downstream voice signal to the downstream data signal [Fig. 6].

9. Claims 8-9 and 19-20 are rejected under 35 U.S.C. 103(a) as being unpatentable over the combination of Lee and Zhou et al as applied to claims 7 and 13 respectively above, and further in view of Booth et al [US 5,835,533].

Regarding claim 8, the combination of Lee and Zhou et al does not teach explicitly a metering signal cancellation circuit.

Booth et al teach a metering signal cancellation circuit (i.e. adaptive filter) shown in Fig. 7, wherein the metering signal cancellation circuit substantially cancels any metering signal present in the upstream voice signal [Fig. 7; col. 1, lines 11-49; col. 7, lines 21-55].

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine Booth et al with the combination of Zhou et al and Lee in order to accommodate signals in the upstream direction so that the network can then serve for communication metering signals [Booth et al; col. 1, lines 29-35].

Claim 19 is essentially similar to claim 8 and is rejected for the reasons stated above.

Regarding claim 9, Booth et al teach the apparatus, wherein the metering signal cancellation circuit further comprises a finite impulse response filter responsive to the metering signal provided to the driver circuitry [Fig. 7; col. 7, lines 21-35].

Claim 20 is essentially similar to claim 9 and is rejected for the reasons stated above.

Conclusion

10. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Ramnandan Singh whose telephone number is (571) 272-7529. The examiner can normally be reached on M-TH (8:00-5:30).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Fan Tsang can be reached on (571) 272-7547. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/749,867 Page 13

Art Unit: 2646

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Ramnandan Singh Examiner Art Unit 2646